

---

**1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

---

**1.1 Product identifier**

**Product name** EST-FASTBLACK  
**Synonyms** EST - FASTBLACK

**1.2 Uses and uses advised against**

**Uses** INDUSTRIAL APPLICATIONS • SPECIALTY CHEMICAL • SURFACE FINISHING

**1.3 Details of the supplier of the product**

**Supplier name** DUBOIS CHEMICALS AUSTRALIA PTY LIMITED  
**Address** 305 Frankston Dandenong Rd, Dandenong South, VIC, 3175, AUSTRALIA  
**Telephone** (03) 9768 3860  
**Email** [sales@duboischchemicals.com.au](mailto:sales@duboischchemicals.com.au)  
**Website** <http://duboischchemicals.com.au/>

**1.4 Emergency telephone numbers**

**Emergency** 13 11 26 (Poisons Information Centre)

---

**2. HAZARDS IDENTIFICATION**

---

**2.1 Classification of the substance or mixture**

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**Physical Hazards**

Not classified as a Physical Hazard

**Health Hazards**

Skin Sensitisation: Category 1  
Carcinogenicity: Category 2  
Specific Target Organ Toxicity (Repeated Exposure): Category 2

**Environmental Hazards**

Not classified as an Environmental Hazard

**2.2 GHS Label elements**

**Signal word** WARNING

**Pictograms****Hazard statements**

H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.

**Prevention statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

## PRODUCT NAME EST-FASTBLACK

### Response statements

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P321 Specific treatment is advised - see first aid instructions.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

### Storage statements

P405 Store locked up.

### Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.

### 2.3 Other hazards

No information provided.

---

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

---

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
COPPER	7440-50-8	231-159-6	<1%
NICKEL	7440-02-0	231-111-4	<1%
SELENIUM	7782-49-2	231-957-4	<1%

---

## 4. FIRST AID MEASURES

---

### 4.1 Description of first aid measures

**Eye** If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

**Inhalation** If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

**Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

**First aid facilities** Eye wash facilities and safety shower should be available.

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

---

## 5. FIRE FIGHTING MEASURES

---

### 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

### 5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases (nickel oxides) if strongly heated.

### 5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

### 5.4 Hazchem code

None allocated.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

## PRODUCT NAME EST-FASTBLACK

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

### 6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

---

## 7. HANDLING AND STORAGE

---

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances and foodstuffs. Ensure containers are adequately labelled and tightly closed when not in use.

### 7.3 Specific end uses

No information provided.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Copper (fume)	SWA [AUS]	--	0.2	--	--
Copper (fume, dusts & mists)	SWA [Proposed]	--	0.01	--	--
Copper, dusts & mists (as Cu)	SWA [AUS]	--	1	--	--
Nickel, metal	SWA [AUS]	--	1	--	--
Nickel, soluble compounds (as Ni)	SWA [AUS]	--	0.1	--	--
Selenium compounds (as Se)	SWA [AUS]	--	0.1	--	--

#### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas.

#### PPE

<b>Eye / Face</b>	Wear splash-proof goggles.
<b>Hands</b>	Wear PVC or rubber gloves.
<b>Body</b>	When using large quantities or where heavy contamination is likely, wear coveralls.
<b>Respiratory</b>	Where an inhalation risk exists, wear a Class P2 (Particulate) respirator.



---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

**9.1 Information on basic physical and chemical properties**

Appearance	BLUE LIQUOD
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	3.5 to 4.0
Vapour density	NOT AVAILABLE
Relative density	1.18
Solubility (water)	SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

**10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

Nickel is attacked slowly by sulphuric or dilute hydrochloric acid; it is readily attacked by nitric acid. Evolving highly flammable hydrogen gas. Under special conditions nickel can react with carbon monoxide in reducing atmospheres to form Nickel Carbonyl, a toxic gas. Very finely divided nickel in the fully reduced state can smoulder in the presence of oxygen or air.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Polymerization will not occur.

**10.4 Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites) and acids (e.g. nitric acid).

**10.6 Hazardous decomposition products**

May evolve toxic gases if heated to decomposition.

**11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity** May be harmful if swallowed, in contact with skin, and/or if inhaled.

**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
COPPER	--	> 2000 mg/kg (rat)	--
NICKEL	> 9000 mg/kg (Sprague-Dawley rat)	--	--
SELENIUM	6700 mg/kg (rat)	--	--

**Skin** Contact may result in irritation, delayed dermatitis resulting from sensitisation ('nickel itch'), skin eruptions, ulcers and pigmentation.

**Eye** Contact may result in irritation, lacrimation, pain and redness.

**Sensitisation** May cause an allergic skin reaction. This product is not classified as a respiratory sensitiser.

**Mutagenicity** Insufficient data available to classify as a mutagen.

**PRODUCT NAME EST-FASTBLACK**

<b>Carcinogenicity</b>	Nickel, metallic and alloys are classified as possibly carcinogenic to humans (IARC Group 2B).
<b>Reproductive</b>	Insufficient data available to classify as a reproductive toxin.
<b>STOT - single exposure</b>	No relevant or reliable studies were identified.
<b>STOT - repeated exposure</b>	Repeated exposure to nickel and its compounds via inhalation may produce respiratory irritation and degeneration in humans (particles under 0.1mm diameter). Prolonged exposure via inhalation to high concentrations may result in lung fibrosis. This product contains selenium, which is required in small quantities for good growth. Selenium is not readily excreted and may build to dangerous levels if exposure is excessive.
<b>Aspiration</b>	Not classified as causing aspiration.

**12. ECOLOGICAL INFORMATION****12.1 Toxicity**

No known ecological effects.

**12.2 Persistence and degradability**

Does not persist in the environment.

**12.3 Bioaccumulative potential**

Does not bioaccumulate.

**12.4 Mobility in soil**

Soluble in water. Highly mobile in soils.

**12.5 Other adverse effects**

Avoid contamination of drains and waterways.

**13. DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

**Waste disposal** Solutions: Cover with sodium carbonate (soda ash), lime or similar alkali to ensure pH greater than 8.5. Collect precipitated solids in sealable containers and label accordingly. Solids: Dampen if necessary and avoid dust generation. Collect solids and store in sealable labelled containers. Absorb with soil and contact the manufacturer for disposal instructions.

**Legislation** Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION****NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA**

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	None allocated.	None allocated.	None allocated.
<b>14.2 Proper Shipping Name</b>	None allocated.	None allocated.	None allocated.
<b>14.3 Transport hazard class</b>	None allocated.	None allocated.	None allocated.
<b>14.4 Packing Group</b>	None allocated.	None allocated.	None allocated.

**14.5 Environmental hazards**

No information provided.

**14.6 Special precautions for user**

**Hazchem code** None allocated.

**15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**PRODUCT NAME EST-FASTBLACK**

<b>Classifications</b>	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).
<b>Inventory listings</b>	<b>AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)</b> All components are listed on AIIC, or are exempt.

---

**16. OTHER INFORMATION**

---

**Additional information** NICKEL: Reported and potential adverse health effects associated with occupational exposure to Nickel metal and inorganic compounds include; an increased risk of nasal, lung and possibly laryngeal cancer in nickel refinery workers; increased risk of gastric cancer; increased risk of sarcoma (cancer arising from connective tissue); severe irritation of the upper respiratory tract; pulmonary irritation and fibrosis; pneumoconiosis; bronchial asthma; increased susceptibility to respiratory infections; dermatitis and skin sensitisation.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

<b>Abbreviations</b>	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
	GHS	Globally Harmonized System
	GTEPG	Group Text Emergency Procedure Guide
	IARC	International Agency for Research on Cancer
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m <sup>3</sup>	Milligrams per Cubic Metre
	OEL	Occupational Exposure Limit
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	SWA	Safe Work Australia
	TLV	Threshold Limit Value
	TWA	Time Weighted Average

**PRODUCT NAME EST-FASTBLACK**

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**