

---

**1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

---

**1.1 Product identifier**

**Product name** TRIPASS ELV 2000  
**Synonyms** TRIPASS ELV2000

**1.2 Uses and uses advised against**

**Uses** INDUSTRIAL APPLICATIONS • SURFACE TREATMENT

**1.3 Details of the supplier of the product**

**Supplier name** DUBOIS CHEMICALS AUSTRALIA PTY LIMITED  
**Address** 305 Frankston Dandenong Rd, Dandenong South, VIC, 3175, AUSTRALIA  
**Telephone** (03) 9768 3860  
**Email** [sales@duboischchemicals.com.au](mailto:sales@duboischchemicals.com.au)  
**Website** <http://duboischchemicals.com.au/>

**1.4 Emergency telephone numbers**

**Emergency** 13 11 26 (Poisons Information Centre)

---

**2. HAZARDS IDENTIFICATION**

---

**2.1 Classification of the substance or mixture**

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**Physical Hazards**

Not classified as a Physical Hazard

**Health Hazards**

Skin Corrosion/Irritation: Category 1B  
Skin Sensitisation: Category 1  
Serious Eye Damage / Eye Irritation: Category 1  
Respiratory Sensitisation: Category 1  
Carcinogenicity: Category 1B  
Toxic to Reproduction: Category 1B  
Specific Target Organ Toxicity (Repeated Exposure): Category 2

**Environmental Hazards**

Aquatic Toxicity (Acute): Category 1  
Aquatic Toxicity (Chronic): Category 2

**2.2 GHS Label elements**

**Signal word** DANGER

**Pictograms**



**PRODUCT NAME TRIPASS ELV 2000****Hazard statements**

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H350i	May cause cancer by inhalation.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

**Prevention statements**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P284	Wear respiratory protection.

**Response statements**

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P310	Immediately call a POISON CENTRE or doctor/physician.
P321	Specific treatment is advised - see first aid instructions.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.

**Storage statements**

P405	Store locked up.
------	------------------

**Disposal statements**

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

**2.3 Other hazards**

No information provided.

---

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**

---

**3.1 Substances / Mixtures**

Ingredient	CAS Number	EC Number	Content
CHROMIUM NITRATE	13548-38-4	236-921-1	30 to 40%
OXALIC ACID DIHYDRATE	6153-56-6	205-634-3	10 to 20%
COBALT (II) NITRATE	10141-05-6	233-402-1	1 to <10%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

---

**4. FIRST AID MEASURES**

---

**4.1 Description of first aid measures**

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

**PRODUCT NAME TRIPASS ELV 2000**

**Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

**First aid facilities** Eye wash facilities and safety shower should be available.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

**4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

---

**5. FIRE FIGHTING MEASURES**

---

**5.1 Extinguishing media**

Use an extinguishing agent suitable for the surrounding fire.

**5.2 Special hazards arising from the substance or mixture**

Non flammable. May evolve toxic gases (carbon / nitrogen / metal oxides) when heated to decomposition. May evolve flammable hydrogen gas in contact with some metals.

**5.3 Advice for firefighters**

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**5.4 Hazchem code**

2X  
2 Fine Water Spray.  
X Wear liquid-tight chemical protective clothing and breathing apparatus. Contain spill and run-off.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

**6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

**7. HANDLING AND STORAGE**

---

**7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well ventilated area, removed from incompatible substances and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation systems. Store between 5°C and 40°C.

**7.3 Specific end uses**

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Cobalt (metal and inorganic)	SWA [Proposed]	--	0.02	--	--
Cobalt, metal dust & fume (as Co)	SWA [AUS]	--	0.05	--	--

#### Biological limits

Ingredient	Determinant	Sampling Time	BEI
COBALT (II) NITRATE	Cobalt in urine	End of shift at end of workweek	15 µg/L

Reference: ACGIH Biological Exposure Indices

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. In a laboratory situation use under a fume cupboard or other localised extraction ventilation equipment.

#### PPE

- Eye / Face** Wear splash-proof goggles. When using large quantities or where heavy contamination is likely, wear a faceshield.
- Hands** Wear butyl or viton® or neoprene gloves.
- Body** Wear coveralls. When using large quantities or where heavy contamination is likely, wear PVC boots.
- Respiratory** Where an inhalation risk exists, wear a Type AB (Organic and Inorganic gases/vapours) respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	VIOLET LIQUID
Odour	MILD ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	> 100°C
Melting point	< 2.77°C
Evaporation rate	NOT AVAILABLE
pH	< 1
Vapour density	NOT AVAILABLE
Relative density	1.38
Solubility (water)	SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

### 9.2 Other information

**9.2 Other information**

VOC

0 g/L

**10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

Carefully review all information provided in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Polymerization will not occur.

**10.4 Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites), alkalis (e.g. sodium hydroxide) and metals.

**10.6 Hazardous decomposition products**

May evolve carbon oxides and hydrocarbons when heated to decomposition.

**11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity** Ingestion may result in severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
CHROMIUM NITRATE	3250 mg/kg (rat)	--	--
OXALIC ACID DIHYDRATE	425 mg/kg (AICIS)	--	--
COBALT (II) NITRATE	434 mg/kg (rat)	--	--

**Skin** Causes severe burns. Contact may result in irritation, redness, pain, rash, dermatitis and severe burns. Effects may be delayed.

**Eye** Causes severe burns. Contact may result in irritation, lacrimation, pain, redness, corneal burns and serious eye damage.

**Sensitisation** May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Mutagenicity** Not classified as a mutagen.

**Carcinogenicity** May cause cancer. Cobalt and cobalt compounds are classified as possibly carcinogenic to humans (IARC Group 2B). There is inadequate evidence in experimental animals for the carcinogenicity of chromium (III) compounds (IARC Monograph, Volume 49).

**Reproductive** Cobalt nitrate is classified as damaging to fertility.

**STOT - single exposure** Over exposure may result in mucous membrane irritation of the respiratory tract, coughing and possible burns. High level exposure may result in ulceration of the respiratory tract, breathing difficulties, chemical pneumonitis and pulmonary oedema.

**STOT - repeated exposure** Repeated exposure to cobalt compounds may result in liver, kidney, lung and heart damage.

**Aspiration** This product does not present an aspiration hazard.

**12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No information provided.

**12.3 Bioaccumulative potential**

No information provided.

**12.4 Mobility in soil**

No information provided.

**12.5 Other adverse effects**

Avoid release to the environment.

**13. DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

**Waste disposal**

Wearing the personal protective equipment outlined above, dilute with water and neutralise with sodium carbonate (soda ash) or sodium bicarbonate. Wash to drain with a large excess of water. Alternatively, mix with a flammable solvent and burn in an incinerator equipped with afterburner and scrubber. Contact the manufacturer/supplier for additional information (if required).

**Legislation**

Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION**

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	3264	3264	3264
<b>14.2 Proper Shipping Name</b>	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains chromium nitrate, cobalt (II) nitrate and oxalic acid)	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains chromium nitrate, cobalt (II) nitrate and oxalic acid)	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains chromium nitrate, cobalt (II) nitrate and oxalic acid)
<b>14.3 Transport hazard class</b>	8	8	8
<b>14.4 Packing Group</b>	II	II	II

**14.5 Environmental hazards**

Marine Pollutant.

**14.6 Special precautions for user**

Hazchem code 2X  
EmS F-A, S-B

**15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule**

Classified as a Schedule 6 (S6) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications**

Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings**      **AUSTRALIA: AIC (Australian Inventory of Industrial Chemicals)**  
All components are listed on AIC, or are exempt.  
**UNITED STATES: TSCA (US Toxic Substances Control Act)**  
All components are listed on the TSCA inventory, or are exempt.

---

## 16. OTHER INFORMATION

---

**Additional information**      **RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**ACIDS:** When mixing acids with water (diluting), caution must be taken as heat will be generated which causes violent spattering. Always add a small volume of acid to a large volume of water, NEVER the reverse.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**  
The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**  
It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

<b>Abbreviations</b>	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
	GHS	Globally Harmonized System
	GTEPG	Group Text Emergency Procedure Guide
	IARC	International Agency for Research on Cancer
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m <sup>3</sup>	Milligrams per Cubic Metre
	OEL	Occupational Exposure Limit
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	SWA	Safe Work Australia
	TLV	Threshold Limit Value
	TWA	Time Weighted Average

**PRODUCT NAME TRIPASS ELV 2000**

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**