

**SECTION 1: Identification**
**1.1. GHS Product identifier**

Product form : Mixture  
 Product name : CIMTAP  
 Product code : B00401

**1.2. Other means of identification**

No additional information available

**1.3. Recommended use of the chemical and restrictions on use**

Recommended use : Tapping paste  
 Restrictions on use : Product for industrial use only

**1.4. Details of manufacturer or importer**
**Manufacturer**

DuBois Chemicals, Inc  
 3630 E. Kemper Road  
 Cincinnati, OH 45241  
 USA  
 T +1-800-438-2647  
[SDS@DuBoisChemicals.com](mailto:SDS@DuBoisChemicals.com) - <https://www.duboischemicals.com/>

**Importer / Distributor**

DuBois Chemicals Australia  
 305 Frankston Dandenong Road  
 DANDENONG SOUTH VIC 3164  
 Australia  
 T +61-3-8340-3222  
[www.duboischemicals.com.au](http://www.duboischemicals.com.au)

**1.5. Emergency phone number**

No additional information available

**SECTION 2: Hazard identification**
**2.1. Classification of the hazardous chemical**
**Classification according to the model Work Health and Safety Regulations (WHS Regulations)**

Serious eye damage/eye irritation, Category 2A	H319
Reproductive toxicity, Additional category, Effects on or via lactation	H362
Hazardous to the aquatic environment – Acute Hazard, Category 1	H400
Hazardous to the aquatic environment – Chronic Hazard, Category 1	H410

**2.2. GHS Label elements, including precautionary statements**

Hazard pictograms (GHS AU) :



Exclamation mark Environment

Signal word (GHS AU) :

Warning

Contains :

Chlorinated paraffins, C14-17 (20 – 40 %); Sulfonic acids, petroleum, sodium salts (5 – 10 %); Fatty acids, tall-oil, reaction products with ethanolamine (1 – 5 %)

Hazard statements (GHS AU) :

H319 - Causes serious eye irritation  
 H362 - May cause harm to breast-fed children  
 H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS AU) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  
 P263 - Avoid contact during pregnancy and while nursing.  
 P264 - Wash hands, forearms and face thoroughly after handling.  
 P270 - Do not eat, drink or smoke when using this product.

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P391 - Collect spillage.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Spill area may be slippery. Do not allow material to contaminate ground water system.

## SECTION 3: Composition and information on ingredients

Name	CAS-No.	Conc. (% w/w)	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Chlorinated paraffins, C14-17	85535-85-9	20 – 40	Lact., H362 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Distillates (petroleum), hydrotreated light naphthenic; Baseoil— unspecified; <3% DMSO	64742-53-6	5 – 10	Not classified
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; <3% DMSO	64742-54-7	1 – 5	Not classified
Fatty acids, tall-oil, reaction products with ethanolamine	68440-25-5	1 – 5	Eye Dam. 1, H318 Aquatic Acute 3, H402
Other substances (not contributing to the classification of this product)	-	40 – 73	-

Comments : For further information refer to section 8, 11, 12.

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Seek medical attention if ill effect develops. May cause harm to breast-fed children. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash contaminated clothing before reuse. Wash skin with plenty of water.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Rinse mouth. Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

Self protection of the first-aiders : First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

### 4.2. Symptoms caused by exposure

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : May cause slight irritation to the skin.

Symptoms/effects after eye contact : Causes serious eye irritation. Eye irritation.

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Symptoms/effects after ingestion : Ingestion may cause nausea, vomiting and diarrhea.  
Chronic symptoms : Prolonged or repeated contact may cause skin to become dry or cracked.

### 4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Any fire extinguishing media may be used on nearby fires (water, powder, foam). Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : The product is not flammable.  
Explosion hazard : No direct explosion hazard.  
General measures : Spill area may be slippery. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.  
Hazardous decomposition products in case of fire : Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulphur oxides. Hydrochloric acid (HCl).

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.  
Hazchem Code : \* 3Z

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Spill area may be slippery. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Ventilate area. Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and materials for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.  
Methods for cleaning up : Take up liquid spill into absorbent material. Sweep or shovel spills into appropriate container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle in accordance with good industrial hygiene and safety practice.
Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Avoid contact during pregnancy/while nursing. Provide good ventilation in process area to prevent formation of vapour. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations. Avoid release to the environment. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Storage conditions	: Keep container closed when not in use. Protect from sunlight. Store in a well-ventilated place. Keep at temperatures between 5°C and 35°C in original container.
Incompatible products	: Strong bases. Strong acids.
Packaging materials	: Always store the product in a container made of the same material as the original container.

### SECTION 8: Exposure controls and personal protection

#### 8.1. Control parameters - exposure standards

Distillates (petroleum), hydrotreated light naphthenic; Baseoil— unspecified; <3% DMSO (64742-53-6)	
Australia - Occupational Exposure Limits	
OES TWA	5 mg/m <sup>3</sup> Distillates (petroleum); Baseoil— unspecified; <3% DMSO [Mist formation; Recommended Limits, ACGIH (American Conference of Governmental Industrial Hygienists), 8 Hours]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; <3% DMSO (64742-54-7)	
Australia - Occupational Exposure Limits	
OES TWA	5 mg/m <sup>3</sup> Distillates (petroleum); Baseoil— unspecified; <3% DMSO [Mist formation; Recommended Limits, ACGIH (American Conference of Governmental Industrial Hygienists), 8 Hours]

#### 8.2. Monitoring methods

No additional information available

#### 8.3. Engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Mist levels should comply with local regulations.
----------------------------------	--

#### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: In case of repeated or prolonged contact wear gloves. Consider the particular working conditions under which the gloves are being used. Follow Cimcool Skin Protection Plan.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0.11		EN ISO 374

Eye protection	: Wear eye protection. Consider the particular working conditions under which the goggles are being used. Safety glasses
----------------	--

Type	Field of application	Characteristics	Standard
Chemical goggles or safety glasses			EN 166

Skin and body protection	: Wear suitable protective clothing. Wash contaminated clothes
--------------------------	--

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

### Personal protective equipment symbol(s)



Environmental exposure controls : Do not discharge into drains or the environment. Avoid release to the environment.

Other information : Avoid contact during pregnancy/while nursing. Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

Physical state : Liquid  
Appearance : paste.  
Colour : white  
Odour : Mild odor Oily  
Odour threshold : No data available  
pH : 8.5 [DIN 51369 (2013); 20°C]  
pH solution concentration : 25 %  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point / Freezing point : Melting point: Not applicable  
Freezing point: < 0 °C (estimated value)  
Boiling point : ≥ 100 °C (estimated value)  
Flash point : > 100 °C Because of the presence of water, a flashpoint cannot be measured.  
Auto-ignition temperature : Not applicable (Contains: Water)  
Decomposition temperature : Not applicable  
Flammability : No data available  
Vapour pressure : Vapour pressure: ≤ 2.33 kPa (Literature data; water, 20°C)  
Relative density : Relative vapour density at 20°C: Not applicable (Mixture)  
Density : Density: 1065 kg/m<sup>3</sup> [DIN 51757/7 (2011); 20°C]  
Solubility : Miscible with water.  
Partition coefficient n-octanol/water (Log Pow) : Not applicable  
Viscosity, kinematic : Paste  
Explosive properties : Not applicable.  
Oxidising properties : Not applicable  
Explosive limits : No data available  
Minimum ignition energy : No data available  
Fat solubility : No data available  
Particle size : Not applicable  
Additional information : The above data are typical values and do not constitute a specification.

## SECTION 10: Stability and reactivity

Reactivity : None reasonably foreseeable.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : None reasonably foreseeable.  
Conditions to avoid : None under recommended storage and handling conditions (see section 7).  
Incompatible materials : Incompatible with strong acids and oxidizing agents. Strong acids. Strong bases.  
Hazardous decomposition products : None under normal use. In case of fire: See Section 5.

## SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

Chlorinated paraffins, C14-17 (85535-85-9)	
LD50 oral rat	2000 – 4000 mg/kg Source: International Uniform Chemical Information Database
LD50 oral	15000 mg/kg

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

<b>Chlorinated paraffins, C14-17 (85535-85-9)</b>	
LD50 dermal rat	> 2800 mg/kg
LD50 dermal rabbit	> 13500 mg/kg bodyweight (24 h, Rabbit, Read-across, Dermal)
<b>Distillates (petroleum), hydrotreated light naphthenic; Baseoil— unspecified; &lt;3% DMSO (64742-53-6)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LD50 dermal	2500 mg/kg
LC50 Inhalation - Rat	2.18 mg/l
LC50 Inhalation - Rat (Dust/Mist)	2.18 mg/l/4h
<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; &lt;3% DMSO (64742-54-7)</b>	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5 mg/l/4h
Skin corrosion/irritation	: Not classified pH: 8.5 [DIN 51369 (2013); 20°C]
Serious eye damage/irritation	: Causes serious eye irritation. pH: 8.5 [DIN 51369 (2013); 20°C]
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: May cause harm to breast-fed children.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
<b>Chlorinated paraffins, C14-17 (85535-85-9)</b>	
NOAEL (oral, rat, 28 days)	23 mg/kg bw/day
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
<b>Distillates (petroleum), hydrotreated light naphthenic; Baseoil— unspecified; &lt;3% DMSO (64742-53-6)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; &lt;3% DMSO (64742-54-7)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Aspiration hazard	: Not classified
<b>CIMTAP</b>	
Viscosity, kinematic	Paste
<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; &lt;3% DMSO (64742-54-7)</b>	
Viscosity, kinematic	≥ 28 – ≤ 30 mm <sup>2</sup> /s @40°C
Potential adverse human health effects and symptoms	: Irritant to the eyes. May cause harm to breast-fed children. Repeated exposure may cause skin dryness or cracking.

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

#### 12.1. Ecotoxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects.
Ecology - water	: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.
Other information	: Avoid release to the environment.

#### Chlorinated paraffins, C14-17 (85535-85-9)

LC50 - Fish [1]	> 5000 mg/l (Equivalent or similar to OECD 203, 96 h, Alburnus alburnus, Static system, Brackish water, Experimental value, Nominal concentration)
LC50 - Fish [2]	> 5000 mg/l Test organisms (species): Alburnus alburnus
EC50 - Crustacea [1]	0.0059 mg/l
ErC50 algae	> 3.2 mg/l
LOEC (chronic)	0.018 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	3400 µg/l
NOEC chronic crustacea	0.0087 mg/l
BCF - Fish [1]	6660 – 9140 l/kg (OECD 305: Bioconcentration: Flow-Through Fish Test, 35 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Kow)	≈ 7 @20°C
Partition coefficient n-octanol/water (Log Pow)	5.47 Source: International Uniform Chemical Information Database
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	5
LD50 dermal rabbit	> 13500 mg/kg bodyweight (24 h, Rabbit, Read-across, Dermal)
LD50 dermal rat	> 2800 mg/kg
LD50 oral rat	2000 – 4000 mg/kg Source: International Uniform Chemical Information Database

#### Distillates (petroleum), hydrotreated light naphthenic; Baseoil— unspecified; <3% DMSO (64742-53-6)

LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

#### Fatty acids, tall-oil, reaction products with ethanolamine (68440-25-5)

LC50 - Fish [1]	5.6 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
-----------------	---

#### Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; <3% DMSO (64742-54-7)

LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; &lt;3% DMSO (64742-54-7)</b>	
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
LD50 oral rat	> 15000 mg/kg Source: IUCLID

### 12.2. Persistence and degradability

<b>CIMTAP</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.
Chemical oxygen demand (COD)	11 g O <sub>2</sub> /l @1%

<b>Chlorinated paraffins, C14-17 (85535-85-9)</b>	
Persistence and degradability	Not readily biodegradable in the soil, Not readily biodegradable in water.

<b>Distillates (petroleum), hydrotreated light naphthenic; Baseoil— unspecified; &lt;3% DMSO (64742-53-6)</b>	
Persistence and degradability	Not rapidly degradable

<b>Fatty acids, tall-oil, reaction products with ethanolamine (68440-25-5)</b>	
Persistence and degradability	Rapidly degradable

<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; &lt;3% DMSO (64742-54-7)</b>	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

<b>CIMTAP</b>	
Partition coefficient n-octanol/water (Log Pow)	Not applicable
Bioaccumulative potential	Not established.

<b>Chlorinated paraffins, C14-17 (85535-85-9)</b>	
BCF - Fish [1]	6660 – 9140 l/kg (OECD 305: Bioconcentration: Flow-Through Fish Test, 35 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.47 Source: International Uniform Chemical Information Database
Partition coefficient n-octanol/water (Log Kow)	≈ 7 @20°C
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	5
Bioaccumulative potential	High potential for bioaccumulation (BCF > 5000).

<b>Distillates (petroleum), hydrotreated light naphthenic; Baseoil— unspecified; &lt;3% DMSO (64742-53-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; &lt;3% DMSO (64742-54-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

### 12.4. Mobility in soil

<b>CIMTAP</b>	
Partition coefficient n-octanol/water (Log Pow)	Not applicable

<b>Chlorinated paraffins, C14-17 (85535-85-9)</b>	
Ecology - soil	Low potential for mobility in soil.
Partition coefficient n-octanol/water (Log Pow)	5.47 Source: International Uniform Chemical Information Database
Partition coefficient n-octanol/water (Log Kow)	≈ 7 @20°C

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Chlorinated paraffins, C14-17 (85535-85-9)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	5
Distillates (petroleum), hydrotreated light naphthenic; Baseoil— unspecified; <3% DMSO (64742-53-6)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; <3% DMSO (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

### 12.5. Other adverse effects

Ozone : Not classified  
 Other adverse effects : No additional information available

CIMTAP	
Fluorinated greenhouse gases	False

## SECTION 13: Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.  
 Waste treatment methods : Recycling is preferred to disposal or incineration. Dispose of contents/container in accordance with licensed collector's sorting instructions.  
 Sewage disposal recommendations : Do not empty into drains. Disposal must be done according to official regulations.  
 Product/Packaging disposal recommendations : Recycle the material as far as possible. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Disposal must be done according to official regulations.  
 Additional information : To be disposed of as hazardous waste. Packaging that is not properly emptied must be disposed of as the unused product. Do not re-use empty containers.  
 Ecological waste information : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
<b>14.1. UN number</b>		
3082	3082	3082
<b>14.2. UN Proper Shipping Name</b>		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Chlorinated paraffins, C14-17)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (chlorinated paraffins, C14-17)	Environmentally hazardous substance, liquid, n.o.s. (chlorinated paraffins, C14-17)
<b>Transport document description</b>		
Not applicable	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (chlorinated paraffins, C14-17), 9, III	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (chlorinated paraffins, C14-17), 9, III
<b>14.3. Transport hazard class(es)</b>		
9	9	9

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

ADG	IMDG	IATA
<b>14.4. Packing group</b>		
III - Substances presenting low danger	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 3082  
Special provision (ADG) : 274, 331, 335, 375, AU01  
Limited quantities (ADG) : 5I  
Excepted quantities (ADG) : E1  
Packing instructions (ADG) : P001, IBC03, LP01  
Special packing provisions (ADG) : PP1  
Portable tank and bulk container instructions (ADG) : T4  
Portable tank and bulk container special provisions (ADG) : TP1, TP29

#### Transport by sea

UN-No. (IMDG) : 3082  
Special provisions (IMDG) : 274, 335, 375, 969  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : LP01, P001  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP29  
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE  
EmS-No. (Spillage) : S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS  
Stowage category (IMDG) : A

#### Air transport

UN-No. (IATA) : 3082  
PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y964  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 964  
PCA max net quantity (IATA) : 450L  
CAO packing instructions (IATA) : 964  
CAO max net quantity (IATA) : 450L  
Special provisions (IATA) : A97, A158, A197, A215  
ERG code (IATA) : 9L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : \* 3Z

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations

##### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : All the chemicals contained in this product are listed introductions Inventory) status

##### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Not applicable

##### Australian Pesticides and Veterinary Medicines Authority (APVMA)

Not applicable

Global Inventories:

Australian Inventory of Industrial Chemicals (AICIS)	All substances are listed
New Zealand Inventory of Chemicals ( NZIoC )	Listed (Alkanes, C14-17, chloro; Distillates (petroleum), hydrotreated light naphthenic; Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; <3% DMSO)

#### 15.2. International agreements

No additional information available

### SECTION 16: Other information

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Abbreviations and acronyms	: ADR - Accord Dangereux Routier (European regulations concerning the international transport of dangerous goods by road) ATE - Acute Toxicity Estimate BCF - Bioconcentration factor CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 DMEL - Derived Minimal Effect level DNEL - Derived-No Effect Level EC50 - Median effective concentration IARC - International Agency for Research on Cancer IMDG - International Maritime Dangerous Goods LC50 - Median lethal concentration LD50 - Median lethal dose LOAEL - Lowest Observed Adverse Effect Level NOAEC - No-Observed Adverse Effect Concentration NOAEL - No-Observed Adverse Effect Level NOEC - No-Observed Effect Concentration OECD - Organisation for Economic Co-operation and Development PBT - Persistent Bioaccumulative Toxic PNEC - Predicted No-Effect Concentration REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 SDS - Safety Data Sheet vPvB - Very Persistent and Very Bioaccumulative
Revision date	: 4/1/2026
Other information	: None.

Classification	
Eye Irrit. 2A	H319
Lact.	H362
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

# CIMTAP

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

---

Full text of H-statements	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Acute 3	Hazardous to the aquatic environment – Acute Hazard, Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Lact.	Reproductive toxicity, Additional category, Effects on or via lactation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H362	May cause harm to breast-fed children
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.